

## Dostępne stopy dla kulek lutowych

Średnica * μm	Tolerancja *	Nie zawierające ołowi (Pb Free)						Zawierające ołów (Pb)						
		Sn94.3Ag5Cu0.7 [217°C]	Sn96.5Ag3Cu0.5 [217°C]	Sn95.5Ag4Cu0.5 [217°C]	Sn98.5Ag1Cu0.5 [217-227°C]	Sn96.5Ag3.5 [221°C]	Sn95Sb5 [232-240°C]	Sn62Pb36Ag2 [179°C]	Sn63Pb37 [183°C]	Sn5Pb85Sb10 [240-256°C]	Sn10Pb88Ag2 [268-292°C]	Sn10Pb90 [275-302°C]	Sn5Pb92.5Ag2.5 [287-296°C]	Sn5Pb95 [308-312°C]
50 μm	± 3 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
60 μm	± 3 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
80 μm	± 4 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
100 μm	± 5 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
150 μm	± 5 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
250 μm	± 5 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
300 μm	± 10 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
350 μm	± 10 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
400 μm	± 10 μm	+	+	+	+	+	+	+	+	+	+	+	+	+
500 μm	± 12 μm	+	+	+	+	+	+	+	+	+	+	+	+	+

\* Ciaśniejsze tolerancje są dostępne na życzenie