



AQUENCE PS

Henkel Pressure Sensitive Adhesives: Waterbased Solutions for Labels

- » Comprehensive product range for a wide spectrum of applications
- » Extensive in-house analytical laboratory test facilities for process & application excellence
- » In-house analytics & lab-testing for highest quality & safety

Henkel Waterbased PSA for Labels

Tailored solutions to fulfill your needs

Application fields	Product	Key features	Viscosity at 25°C (mPas)	Solids Content (%)
Removable	AQUENCE PS 6090-10	<ul style="list-style-type: none"> » Best in class removable for paper and filmic face stocks » Successful globally » Stable adhesion over time » Smooth removability 	400 – 900 (RV, 50 rpm)	59 – 61
	AQUENCE PS 6090-16	<ul style="list-style-type: none"> » Ultra removable version of 6090-10 » Better low temperature performance 	180 – 300* (RV, 20 rpm)	54,5 – 57,5
Permanent Paper Labels	AQUENCE PS 6014	<ul style="list-style-type: none"> » Permanent adhesive for general purpose paper labels » Highly cohesive pure acrylic adhesive » Excellent die-cuttability » Compatible with a wide range of tackifiers » Good adhesion on surfaces with condensation 	200 – 800 (RV, 50 rpm)	59 – 61
Pharmaceutical Labelling	AQUENCE PS 3314 U-C	<ul style="list-style-type: none"> » Excellent for small diameter bottles » Unique balance of adhesion and cohesion preventing label flagging » Henkel food contact statement available » Good adhesion on both polar and non polar surfaces » High clarity 	100 – 600 (RV, 30 rpm)	58 – 62
Water Resistant Clear on, Clear, Labels	AQUENCE PS 3312	<ul style="list-style-type: none"> » Unique non-water whitening adhesive » Superior water resistance » Global leader » Suitable for high speed coating » Excellent die-cuttability » Good adhesion to a variety of substrates » Recommended for beverage and household applications » Henkel food contact statement available 	250 – 400 (RV, 50 rpm)	51 – 53

Contact us for more information:

Henkel AG & Co. KGaA
Henkelstraße 67
40191 Düsseldorf, Germany
Phone: +49 211 797-5505

Fax: +49 211 798-15505
Email: psa@henkel.com
www.henkel.com

