



## Adhesive Solutions for Corrugated Boxes

### Match for Toughest Wear and Tear

- » High wet tack
- » Precision gluing
- » Reliable bonding
- » Fast setting speed
- » Water resistant
- » Easy cleaning



# Adhesive Solutions for Corrugated Boxes

## Match for Toughest Wear and Tear

### NOZZLE APPLICATION

PRODUCT	VISCOSITY	SETTING TIME	SUITABLE SUBSTRATES
AQUENCE FB 9001 LM	850 mPa.s	Fast	PE coated paper. Not for UV varnished.
AQUENCE FB 9003 LM	1,800 mPa.s	Fast	PE coated paper. Not for UV varnished.
AQUENCE FB 2225	900 mPa.s	Fast	Unvarnished
AQUENCE CG 2354	1,800 mPa.s	Fast	Unvarnished
AQUENCE CG 15511	3,750 mPa.s	Fast	Unvarnished


### WHEEL APPLICATION

PRODUCT	VISCOSITY	SETTING TIME	SUITABLE SUBSTRATES
AQUENCE FB 264	4,500 mPa.s	Fast	Varnished
AQUENCE BG 2323	4,500 mPa.s	Fast	Unvarnished
AQUENCE LA 4511	3,000 mPa.s	Fast	Unvarnished

### SPECIALTIES

PRODUCT	VISCOSITY	SETTING TIME	SUITABLE SUBSTRATES
AQUENCE CG 14050 Red	9 – 12 sec (Ford)	n/a	Additive for starch-based adhesives

**eco+** Ask us for our eco+ solutions.  
Your measurable advantage in performance and sustainability.



### Contact us for more information:

Europe, Middle East, Africa  
Henkel AG & Co. KGaA  
Phone: +49 211 797-7486

North America  
Henkel Corporation  
Phone: +1 860 571-5100

South America  
Henkel Ltda.  
Phone: +55 11 3205-8955

Asia  
Henkel (China) Co. Ltd.  
Phone: +86 21 2891-8000

[paper.converting@henkel.com](mailto:paper.converting@henkel.com) | [www.henkel.com](http://www.henkel.com)



The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention. The information is protected by copyright. In particular, any reproductions, adaptations, translations, storage and processing in other media, including storage or processing by electronic means, enjoy copyright protection. Any exploitation in whole or in part thereof shall require the prior written consent of Henkel AG & Co. KGaA. Except as otherwise noted, all marks used in this sell sheet are trademarks and/or registered trademarks of Henkel and/or its affiliates in the US, Germany, and elsewhere. © Henkel AG & Co. KGaA, 04/2014